

LED FLOODLIGHT FAMILY (S-SERIES)

L20WFL01S
L30WFL01S



Features

- Energy efficient LED floodlight
- Low energy consumption compared to traditional HID floodlights
- Longer lamp lifespan
- High brightness
- Die-cast aluminium casing, IP65
- Environment-friendly materials
- Low heat emissions
- Lower maintenance requirements and cost
- Compact size
- Instant start and restart. No more waiting for ignition
- Flexible installation
- Reduce waste
- Choice of color temperature (6000K, 3000K)
- Available in 20W and 30W versions

Applications

- Architectural Lighting
- High-security areas
- Home security lighting
- Commercial lighting
- Stage lighting



Distributed by:
Denki Shoji Sdn. Bhd. (758673-V)
12, Jalan Perdana 6/8, Pandan Perdana,
55300 Kuala Lumpur, Malaysia.
Tel: 03-9282 2993 / 9285 2993
Fax: 03-9283 8993
Email: inquiry@oro-p.com

ORO-P™
www.oro-p.com

Specifications

Power (Watts)	20W
Voltage (AC, V)	85-265V, 50/60Hz
Voltage (DC, V)	18-36V
Current (A)	0.60A
Power Factor (PF)	0.65
Dimensions (Width, Height, Depth)	180 x 140 x 105 mm
Weight (KG)	2.0KG



Distributed by:
Denki Shoji Sdn. Bhd. (758673-V)
12, Jalan Perdana 6/8, Pandan Perdana,
55300 Kuala Lumpur, Malaysia.
Tel: 03-9282 2993 / 9285 2993
Fax: 03-9283 8993
Email: inquiry@oro-p.com

ORO-P™
www.oro-p.com

Specifications

Power (Watts)	30W
Voltage (AC, V)	85-265V, 50/60Hz
Voltage (DC, V)	18-36V
Current (A)	0.90A
Power Factor (PF)	0.65
Dimensions (WidthxHeightxDepth)	225 x 185 x 128 mm
Weight (KG)	2.5KG



Distributed by:
Denki Shoji Sdn. Bhd. (758673-V)
12, Jalan Perdana 6/8, Pandan Perdana,
55300 Kuala Lumpur, Malaysia.
Tel: 03-9282 2993 / 9285 2993
Fax: 03-9283 8993
Email: inquiry@oro-p.com

ORO-P™
www.oro-p.com